

RELIFE MELANGE (RFM) – kategorie B

Váha (g/m ²) – <i>Weight (g/m²)</i>	EN 12127	± 5 %	330
Výška (cm) – <i>Width (cm)</i>	-----	± 2 %	140
Otěruvzdornost (cykly) <i>Abrasion resistance (rubs)</i>	EN ISO 12947-2 (Martindale)		100.000
Barevná stálost na světle (modrá stupnice) <i>Light fastness (blue scale)</i>	ISO 105-B02 (Xenotest)		4/5
Stálost barvy při otěru (stupnice šedé) <i>Fastness to rubbing (grey scale)</i>	ISO 105-X12 (Crockmeter)		4/5
Pilling (2000 cyklů) – <i>Pilling (2000 rubs)</i>	ISO 12945-2		4/5
Akustická absorpce – <i>Acoustic absorbtion</i>	EN ISO 10534-2		0.9
Složení – <i>Composition</i>	75% recyklovaný polyester / 25% polyester (100% post consumer polyester / 25% polyester)		
Všechny certifikáty – <i>Certificates available</i>			
EN 1021 1/2 BS 5852 0 BS 7176 Low Hazard CAL TB 117 Section 1 NFPA 260 Class 1 IMO MSC.307 (88) Annex I Part 8 <i>available at antares.cz</i>			
Čištění a údržba potahů – <i>Cleaning and washing</i>			
<i>Vacuum regularly. In case of stains, use a damp cloth with neutral soap suitable for cleaning of upholstery products.</i>			

RELIFE MELANGE (RFM) – kategorie B

Dostupné ve 14 barvách / Available in 14 colors




RFM101




RFM102



RFM103



RFM104



RFM105



RFM107




RFM108



RFM111



RFM112



RFM113




RFM114



RFM116



RFM117



RFM118

